Environmental Protection Agency

gas sample, expressed as exhaust hydrocarbon from petroleum-fueled locomotives. The hydrogen-to-carbon ratio of the equivalent hydrocarbon is 1.85:1.

Ultimate purchaser means, with respect to any new vessel or new marine engine, the first person who in good faith purchases such new vessel or new marine engine for purposes other than resale.

Ultra low-sulfur diesel fuel means one of the following:

(1) For in-use fuels, ultra low-sulfur diesel fuel means a diesel fuel marketed as ultra low-sulfur diesel fuel having a maximum sulfur concentration of 15 parts per million.

(2) For testing, ultra low-sulfur diesel fuel has the meaning given in 40 CFR part 1065

United States has the meaning given in 40 CFR 1068.30.

Upcoming model year means for an engine family the model year after the one currently in production.

U.S.-directed production volume means the number of engine units, subject to the requirements of this part, produced by a manufacturer for which the manufacturer has a reasonable assurance that sale was or will be made to ultimate purchasers in the United States.

Useful life means the period during which the engine is designed to properly function in terms of reliability and fuel consumption, without being remanufactured, specified as a number of hours of operation or calendar years, whichever comes first. It is the period during which a new engine is required to comply with all applicable emission standards. See § 1042.101(e).

Variable-speed engine means an engine that is not a constant-speed engine.

Vessel means a marine vessel.

Vessel operator means any individual that physically operates or maintains a vessel or exercises managerial control over the operation of the vessel.

Vessel owner means the individual or company that holds legal title to a vessel.

Void has the meaning given in 40 CFR 1068.30. In general this means to invalidate a certificate or an exemption both retroactively and prospectively.

Volatile liquid fuel means any fuel other than diesel fuel or biodiesel that is a liquid at atmospheric pressure and has a Reid Vapor Pressure higher than 2.0 pounds per square inch.

We (us, our) means the Administrator of the Environmental Protection Agency and any authorized representatives.

§1042.905 Symbols, acronyms, and abbreviations

The following symbols, acronyms, and abbreviations apply to this part:

ABT Averaging, banking, and trading. AECD auxiliary-emission control device.

CFR Code of Federal Regulations. CO carbon monoxide.

CO₂ carbon dioxide.

cyl cylinder.

disp. displacement.

Environmental Protection Agency. EPA

FEL Family Emission Limit.

g grams. HC byd-

hydrocarbon.

hr hours.

kPa kilopascals.

kW kilowatts.

L liters.

LTR Limited Testing Region.

NARA National Archives and Records Administration.

NMHC nonmethane hydrocarbons. NO_X oxides of nitrogen (NO and NO₂).

NTE not-to-exceed.

PM particulate matter.

RPM revolutions per minute.

SAE Society of Automotive Engineers.

SCR selective catalytic reduction.

THC total hydrocarbon.

THCE total hydrocarbon equivalent.

ULSD ultra low-sulfur diesel fuel.

U.S.C. United States Code.

§ 1042.910 Reference materials.

Documents listed in this section have been incorporated by reference into this part. The Director of the Federal Register approved the incorporation by reference as prescribed in 5 U.S.C. 552(a) and 1 CFR part 51. Anyone may inspect copies at the U.S. EPA, Air and Radiation Docket and Information Center, 1301 Constitution Ave., NW., Room B102, EPA West Building, Washington, DC 20460 or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202-741-6030. orgo to: http:// www.archives.gov/federal register/ code of federal regulations/

ibr locations.html.

(a) SAE material. Table 1 to this section lists material from the Society of